

Other advantages in detail:



integrated lights



multi-adjustable live ring



optional: mechanical remote control

Technical Data

Model	HD 15/0-4	HD 15/0-4	HD 18/0-5	HD 18/0-5	HD 21/0-6	HD 24/0-7
	not braked	braked	not braked	braked	braked	braked
Payload [kg]	250	250	250	250	250	250
Permissible total weight (Basic Design) kg	750	1,200	750	1,200	1,200	1,200
Permissible axle load [kg]	750	1,200	750	1,200	1,200	1,200
Dimensions [mm]:						
<u>Length of lift</u>						
Manoeuvring	4,040	4,165	4,090	4,165	4,165	4,165
Driving	4,890	4,900	4,890	4,900	4,900	4,900
<u>Width of lift</u>						
Manoeuvring	870	890	870	890	890	890
Driving	1,299	1,299	1,299	1,299	1,299	1,299
<u>Guide rails</u>						
Package length [mm]	3,950	3,950	4,005	4,005	4,060	4,115
Track width [mm]	540	540	540	540	540	540
extendable from - to [m] approx	3.9 - 15.1	3.9 - 15.1	4.0 - 17.9	4.0 - 17.9	4.1 - 20.9	4.1 - 23.7
Shaft	retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing	retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing
Drive unit	Hydraulic unit 230 V, 2.6 kW, petrol-motor *	Hydraulic unit 230 V, 2.6 kW, petrol-motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*

* Extra

All rights for technical alterations and possible mistakes reserved.

 **Böcker**

Kran- und Aufzugstechnik

Albert Böcker GmbH & Co.KG

Lippestraße 69 · D-59368 Werne · Postfach 1153 · D-59354 Werne

Telefon: 0049 (0)2389/7989-0 · Telefax: 0049 (0)2389/532204

Internet: www.boecker.de · e-mail: vertrieb@boecker.de

Böcker

Junior-
Construction Lift



The new Junior Construction Lift!

The smallest construction lift of all times.



The Junior Construction Lift is suitable for transportation by nearly all types of ordinary motor vehicles

The newly developed **Junior Construction Lift** continues to be the ideal solution for operations in cramped and restricted conditions. In conjunction with its strong performance and its state-of-the-art features the new **Junior** is the ideal construction lift for fast transportation whenever conditions get tight.



application with a mechanical kneejoint (optional)



now up to
zu 250 kg
payload!

it just couldn't be any smaller



Standard axle (solid): 1,3 m



optional: retractable axle: 0,89 m



Optional: mechanical kneejoint



Optional: petrol motor



retractable shaft



even fits through standard size doors

The advantages at a glance:

1. Minimum requirement of space, even when fully assembled
2. Due to its retractable axle, it fits through the narrowest of lanes, if necessary, even through the back entrance
3. Retractable and stake off ball bearing-if it gets really tight
4. Additional radius afforded through extra kneejoints-available as accessory
5. Suitable for transportation by all types of ordinary motor vehicles
6. Extremely reliable and superior operational comfort like all inclined construction lifts made by Böcker



Small - Handy - Powerful - Fast