

Böcker



Junior

Furniture Lift

The new Junior Furniture Lift!

Any smaller than that one?-Hardly possible...

The **Junior** Model of the **Böcker Furniture Lift** Series is so small, narrow, compact and easy to handle that it can pass through the narrowest lanes. Despite this, it still surprises with its very high performance values.



The Junior Construction Lift is suitable for transportation by nearly all types of ordinary motor vehicles



Use in smallest possible space



In some places, the streets are only narrow lanes or the house of the customer can be reached only through the backyard. The entry there is however much too narrow for usual furniture lifts. In many cases there is a great lack of space.

But now there is a solution:
The **Junior Furniture Lift** from **Böcker**. Designed for operation in the smallest possible spaces, it offers sufficient capacity to achieve a great performance even in the smallest spaces available.



now up to
zu 250 kg
payload!



even fits through standard size doors

"Impossible" is not in our
vocabulary...

Advantages at a glance:

1. Smallest possible space demand, even in operational state
2. Fits on account of the slide-in axle through the narrowest lanes, if necessary even through the back door
3. Slide-in and removable ball coupling for situations where it is really narrow
4. Can be pulled also by passenger cars
5. Maximum reliability and operating comfort as with all Böcker furniture lifts

it just couldn't be any smaller



Standard axle (solid): 1,3 m



optional: retractable axle: 0,89 m



retractable shaft



Standard: electro motor



Small - Handy - Powerful - Fast

Other advantages in detail:



integrated lights



multi-adjustable live ring



optional: mechanical remote control

Technical Data

Model	HD 15/0-4	HD 15/0-4	HD 18/0-5	HD 18/0-5	HD 21/0-6	HD 24/0-7
	not braked	braked	not braked	braked	braked	braked
Payload [kg]	250	250	250	250	250	250
Permissible total weight (Basic Design) kg	750	1,200	750	1,200	1,200	1,200
Permissible axle load [kg]	750	1,200	750	1,200	1,200	1,200
Dimensions [mm]:						
<u>Length of lift</u>						
Manoeuvring	3,860	4,165	3,910	4,165	4,165	4,165
Driving	4,890	4,900	4,890	4,900	4,900	4,900
<u>Width of lift</u>						
Manoeuvring	870	890	870	890	890	890
Driving	1,299	1,299	1,299	1,299	1,299	1,299
<u>Guide rails</u>						
Package length [mm]	3,800	3,800	3,855	3,855	3,910	3,965
Track width [mm]	540	540	540	540	540	540
extendable from - to [m] approx	3.80 - 15.00	3.80 - 15.00	3.85 - 17.80	3.85 - 17.80	3.90 - 20.80	3.98 - 23.60
Shaft	retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing	retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing	straight, retractable and traceable with ball bearing
Drive unit	Hydraulic unit 230 V, 2.6 kW, petrol-motor *	Hydraulic unit 230 V, 2.6 kW, petrol-motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*	Hydraulic unit 230 V, 2.6 kW, petrol motor*

* Extra

All rights for technical alterations and possible mistakes reserved.

Bocker

Kran- und Aufzugstechnik

Albert Böcker GmbH & Co.KG

Lippestraße 69 · D-59368 Werne · Postfach 1153 · D-59354 Werne

Telefon: 0049 (0)2389/7989-0 · Telefax: 0049 (0)2389/532204

Internet: www.boecker.de · e-mail: vertrieb@boecker.de